

## DELMIA Version 5 Release 19 Modification Level 0

DELMIA V5.19:

- Introduces the Work Instruction Composer to speed the delivery of work instructions to the shop floor
- Adds capabilities to support the high technology and automotive domains
- Adds key DELMIA Automation products to the Version 5 product lifecycle management (PLM) portfolio
- Supplies new general assembly planning and simulation solutions

## Hardware Requirements

### Summary of DELMIA V5.19 Recommended Configurations

- Oracle server - Any hardware and operating system platform as certified by Oracle
- Manufacturing Hub server
  - Hardware - Any certified server with a 64-bit CPU (Intel® EM64T)
  - Operating system - Microsoft® Windows® Server 2003 R2 SP2 (32 bit)
- DELMIA clients
  - Hardware - Any certified workstation with a 64-bit CPU (Intel EM64T)
  - Operating system

Microsoft Windows XP® Professional SP2 (32 bit)  
Microsoft Windows XP Professional x64 SP2 (64 bit)

A complete list of certified combinations of hardware and software platforms can be found at:

<http://www.3ds.com/support>

### Hardware Requirements for DELMIA Process Detailing and Validation

The following requirements are common to all operating systems supported by this release. Platform-specific requirements are specified in subsequent topics.

- Required components and features
  - **Disk drive:** An internal or external disk drive (minimum recommended size is 80 GB) is required to store program executables, program

data, the user environment, and to supply paging space. Installation of all DELMIA Process Detailing and Validation products requires 2.0 GB on Microsoft Windows, 2.4 GB on AIX®, 2.7 GB on HP-UX, and 2.3 GB on Solaris.

- **Memory:** 1024 MB of RAM is the minimum recommended for all applications. 2048 MB of RAM is recommended for large manufacturing models. Requirements may be greater when large amounts of data are used.
- **Internal/external drives:** A CD-ROM drive is required for program installation and for access to the online documentation, which can optionally be downloaded to disk.
- **Display:** A graphics color display compatible with the selected platform-specific graphics adapter. The minimum recommended size for usability reasons is 17 inches. Minimum resolution for Windows workstations is 1024 x 768 and 1280 x 1024 for UNIX® workstations. When selecting a graphics adapter, hardware texturing capability is strongly recommended when using products that employ texture mapping, in which case the amount of texture RAM has to be adequate for the number and complexity of textures to be used.
- **Keyboard:** A specific keyboard compatible with the selected installation locale may be required for national language support.
- **Pointing device:** Three-button mouse. On Microsoft Windows workstations, a two-button mouse may alternatively be used (the third button is emulated with a keyboard sequence). The three-button mouse is recommended for usability reasons. IntelliMouse (two buttons plus a wheel instead of the third button) is an alternative to the three-button mouse on Windows workstations. The wheel acts as the middle button to allow additional manipulations, such as panning and scrolling.
- **Optional components and features:** For Platform 2 (P2) products, SpaceBall or SpaceMouse, in addition to the standard mouse, can be used to perform graphic manipulations (zoom, pan, and rotate). The required drivers are delivered with these devices. Support of these devices is also available with the DMU Navigator 1 (5674-MDU) Add-on Product.

The robustness of the overall solution is dependent on the robustness of the operating system and the hardware environment used. Configurations certified by Dassault Systemes for running DELMIA Version 5 are published at

<http://www.3ds.com/support>

Although DELMIA Version 5 products might run on configurations or with graphic adapters other than those specified for each of the following platforms, incidents specific to such configurations or adapters will not be accepted for support.

## Microsoft Windows XP 32 bit

- **System unit:** An Intel Pentium® 4 or Xeon® based workstation running Microsoft Windows XP Professional Edition SP2.
- **Graphics adapter:** A graphics adapter with a 3D OpenGL accelerator is required.

**Note:** Graphics performance on local transformations (panning, zooming, and rotating model) will depend on the selected graphics adapter. The graphics adapter should have the following capabilities:

- 24 bits, true color, double buffered visual
  - 24 bits, Z-buffer
  - Stencil buffer
  - Minimum supported resolution: 1024 x 768. A resolution of 1280 x 1024 is recommended for usability reasons.
- **Network adapter:** An active LAN adapter (Ethernet or Token Ring, installed and configured) is required for license key purposes.

## Microsoft Windows x86 64 bit

- **System unit:** An Intel Xeon EM64T or AMD Opteron 64-bit based workstation running Microsoft Windows XP Professional x64 Edition.
- **Memory:** 4 GB is the recommended minimum.
- **Disk drive:** 40 GB is the recommended minimum.
- **Graphics adapter:** A graphics adapter with a 3D OpenGL accelerator is required.

**Note:** Graphics performance on local transformations (panning, zooming, rotating model) will depend on the selected graphics adapter. The graphics adapter should have the following capabilities:

- 24 bits, true color, double buffered visual.
  - 24 bits, Z-buffer.
  - Stencil buffer.
  - Minimum supported resolution: 1024 x 768. A resolution of 1280 x 1024 is recommended for usability reasons.
- **Network adapter:** An active LAN adapter (Ethernet or Token Ring, installed and configured) is required for license key purposes.

## IBM AIX

- **System unit:** Any RS/6000®, based on the Power4, Power5, Power PC-970 processor families, supported on AIX V5.3
- **Graphics adapter:** One of the following graphics adapters is required.
  - GXT500P
  - GXT550P
  - GXT800P
  - GXT800M
  - GXT2000P
  - GXT3000P
  - GXT4000P
  - GXT4500P
  - GXT6000P
  - GXT6500P

## HP-UX

- **System unit:** Any B-Class, C-Class, or J-Class workstation based on the PA8000, PA8800, and PA8900 processor family and supported on HP-UX 11iv1.
- **Graphics adapter:** One of the following graphics adapters is required:
  - Visualize-FXE
  - Visualize-FX2
  - Visualize-FX4
  - Visualize-FX5
  - Visualize-FX6
  - Visualize-FX10
  - Fire GL-UX
  - Fire GL T2-128
  - Fire GL X1
  - Fire GL X3

## Sun™ Solaris

- **System unit:** Any Ultra1, Ultra2, Ultra10, Ultra30, Ultra60, Sun Blade 100, Sun Blade 150, Sun Blade 1000, Sun Blade 1500, Sun Blade 1500+ (1.5 GHz), Sun Blade 2000, or SunBlade 2500 workstation based on the UltraSPARC processor supported on Solaris 10.
- **Graphics adapter:** One of the following graphics adapters is required.
  - Creator3D
  - Creator3D Series III
  - Elite 3D (U10-440MHz only for U10 workstations)
  - Elite 3D Lite
  - Expert 3D
  - XVR-500
  - XVR-600
  - XVR-1000
  - XVR-1200

## Hardware Requirements for Manufacturing Hub Server

Any Microsoft Windows Server 2003® platform as certified by Microsoft.

## Hardware Requirements for DELMIA Process Planning Clients

- **Processor:** Intel Pentium-4, minimum 2400 MHz.
- **Disk drive:** Minimum of 1024 MB; 2048 MB to install a client, server, and an Oracle server on the same machine.
- **Graphical interface:** 1024 x 768 OpenGL with a minimum of 32 MB onboard memory.
- **Network connection:** LAN (completely configured).
- **Communication protocol:** TCP/IP. The machine must have an IP address (either static or via DHCP)

---

# Programming Requirements

## Software Requirements for DELMIA Process Detailing and Validation

### Summary of Changes for V5.19

- Minimum run-time support for IBM AIX running on Power4 or Power5 processors for both 32 bit and 64 bit is provided by AIX 5.3 Technical Level 05 SP 3.
- Minimum run-time support for HP-UX Run-time is HP-UX 11iv1 (11.11) December, 2004 (on 32 bit only).
- Minimum run-time support on Sun Solaris SPARC is Solaris 10 SPARC. The minimum level required is Solaris 10 HW

03/05 with 119280-06 CDE 1.6 - Runtime library patch for Solaris 10.

- The required level for document browsers in a UNIX environment is Mozilla 1.7 for AIX, HP-UX, and Solaris and Firefox 2.0 for Sun Solaris SPARC.
- The required level for document browsers in a Microsoft Windows environment is Microsoft Internet Explorer 7.0.
- The required level for JRE is 1.6.2 for all operating systems.

**Note:** DELMIA V5.19 is the last release to support HP-UX.

### Common Software Requirements

DELMIA Process Detailing and Validation runs on selected levels of:

- Microsoft Windows 32 bit: Windows XP Professional and Windows Vista x86
- Microsoft Windows 64 bit: Windows XP Professional x64 and Windows Vista x64
- IBM AIX
- Hewlett Packard HP-UX 11iv1
- Sun Solaris SPARC

Refer to the Program Directory or contact your Dassault Systemes Support Center for appropriate corrective service to apply to the software described below.

### Software Requirements for Microsoft Windows XP Professional Edition SP2

Windows XP delivers an implementation of OpenGL libraries. These drivers may offer a DELMIA application setting (see Control Panel, Display Properties tabs), which should be selected when available, as they may contain application-specific features. For recommendations related to driver levels based on certified configurations, visit

<http://www.3ds.com/support>

A localized version of the operating system may be required when the selected installation locale differs from Latin 1.

The following software is also required:

- Microsoft Internet Explorer 7
- Sun JRE Version 6 Update 2
- Microsoft .NET Framework Version 3.0 Redistributable Package

### Software Requirements for Microsoft Windows Vista Enterprise Edition (32 bit)

In addition to the operating system, the following software is also required:

- Microsoft Internet Explorer 7
- Sun JRE Version 6 Update 2
- Microsoft .NET Framework Version 3.0 Redistributable Package

### Software Requirements for Microsoft Windows XP Professional x64 Edition SP2

Windows XP Professional x64 Edition delivers an implementation of OpenGL libraries. These drivers may offer a DELMIA application setting (see Control Panel, Display Properties tabs), which should be selected when available, as they may contain application-specific

features. For recommendations related to driver levels based on certified configurations, visit

<http://www.3ds.com/support>

The following software is also required:

- Microsoft Internet Explorer 7
- Sun JRE Version 6 Update 2

### Software Requirements for Microsoft Windows Vista x64 Enterprise Edition (64 bit)

In addition to the operating system, the following software is required:

- Microsoft Internet Explorer 7
- Sun JRE Version 6 Update 2

### Software Requirements for IBM AIX 32-bit and 64-bit platforms

AIX 5.3 Technical Level 05 SP 3 (using 64-bit kernel), with the following components:

- XL C/C++ Enterprise Edition V8.0.0 Run-time Environment
  - April, 2007 IBM C++ Runtime Environment Component for AIX
  - Fileset x1C.aix50.rte at level 8.0.0.
- XL Fortran Enterprise Edition V10.1.0 for AIX Runtime
  - August 2006 XL Fortran V10.1 for AIX Runtime
  - Fileset xlftrte.aix51 at level 10.1.0.2
- OpenGL 1.3 as delivered on AIX CDs
- Mozilla 1.7 browser
- IBM JRE V5 SR6
- IBM Java™ Plug-In V5 SR6

### Software Requirements for HP-UX

**Note:** HP-UX will not be supported in any future DELMIA Version 5 release.

- HP-UX Version 11iv1 (11.11) (December 2004) with the following components:
  - HP-UX Technical Computing OE (TCOE) Component December 2004
  - Mozilla 1.7
  - HP-UX JRE 5.0.10
  - HP-UX Java Plug-In 5.0.10
- HP-UX Version 11iv1 (11.11) (June 2007) with the following components:
  - HP-UX Technical Computing OE (TCOE) Component December 2006
  - Mozilla 1.7
  - HP-UX JRE 5.0.10
  - HP-UX Java Plug-In 5.0.10

### Software Requirements for Sun Solaris

Sun Solaris 10 H/W 03/05, with:

- Firefox 2.0
- Sun JRE Version 6 Update 4
- Sun Java Plug-In Version 6 Update 4

## DELMIA Process Detailing and Validation General Packaging Principles

- A DELMIA P1 product or a DELMIA P1 configuration requires or must include (in the case of configurations) DELMIA - Object Manager 1 (DO1). P1 products can be used on P2, and in such cases, they operate with DELMIA - Object Manager 2 (DOM).
- A DELMIA P2 product or a DELMIA P2 configuration requires, or must include (in the case of configurations), DELMIA - Object Manager 2 (DOM).
- License keys for configurations are acquired and released for the total configuration.
- The functions within a configuration cannot be shared.
- A configuration is required for each DELMIA seat.
- DELMIA add-on and shareable products may require prerequisite products that are not included in a standard purchased configuration. When a prerequisite product is not included in the selected standard configuration, both the AOP and its prerequisite products must be purchased and included as AOPs within a custom configuration. Prerequisites for shareable products can be satisfied by a standard configuration, by an AOP within a custom configuration, or by a shareable product.

## Macro Replay Capabilities

DELMIA has built-in macro record and replay capabilities. For UNIX, the interpreter is VB Script 3.0 from Mainsoft. Its components are included as shared libraries. For Microsoft Windows, the interpreter is Microsoft Visual Basic for Applications (VBA) at a minimum level of 6.0. VBA is delivered and installed by default with DELMIA Process Detailing and Validation.

## Printer and Plotter Support

- UNIX - DELMIA Process Detailing and Validation supports the following plotter/printer languages:
  - CGM-ISO, ATA, CALS
  - Hewlett Packard HP-GL/2-RTL and HP-GL or IBM-GL subsets
  - OCE Graphics GPR50: VDF plotting routines
  - PostScript
- Microsoft Windows - Printers and plotters are supported through the vendor's drivers for the targeted printer or plotter relative to the targeted version of the operating system. Contact the printer or plotter vendor for requirements and support.

## Software Requirements for DELMIA Process Planning

### ENOVIA Manufacturing Hub Server

The Manufacturing Hub server is certified on the following operating systems:

- Microsoft Windows Server 2003 Standard Edition Service Pack 2 (32 bit)
- Microsoft Windows Server 2003 Enterprise Edition Service Pack 2 (32 bit)
- Microsoft Windows Server 2003 Standard Edition R2 Service Pack 2 (32 bit)
- Microsoft Windows Server 2003 Enterprise Edition R2 Service Pack 2 (32 bit)

### DELMIA Process Planning Clients

Process Engineer clients are certified on the following operating systems:

- Microsoft Windows XP Professional Service Pack 2 (32 bit)
- Microsoft Windows XP Professional x64 Service Pack 2 (64 bit)
- Microsoft Windows Vista Enterprise x86 (32 bit)
- Microsoft Windows Vista Enterprise x64 (64 bit)

### Certified Third-Party Software (Windows-based)

- Oracle database - Oracle 10.2.0.2 or later is a prerequisite for the Manufacturing Hub server.
- Java is a prerequisite for:
  - The Manufacturing Hub server
  - Single Sign-On (SSO) on Process Planning clients
  - Manufacturing Hub integration and SSO on Process Detailing and Validation (32 bit and 64 bit)

The required Java level is:

- For Windows 32 bit - Sun JRE Version 6.0 Update 2
- For Windows 64 bit - Sun JRE Version 6.0 Update 2 x64
- Microsoft Visual J# V2.0 and Microsoft .NET Framework 3.0 is a prerequisite for SSO and Web Services for the Manufacturing Hub, and for SSO on Process Planning and Process Detailing and Validation clients.
- FlexLM Version 9.5 is a prerequisite for the licensing environment for the Manufacturing Hub server and Process Planning clients.
- Microsoft Office Excel 2003 is a prerequisite for script-based reporting on Process Planning clients and for DPM Work Instructions on Process Detailing and Validation clients (32 bit and 64 bit).
- Microsoft Internet Explorer 7 is a prerequisite for ErgoCheck on Process Planning clients and for documentation on Process Detailing and Validation clients (32 bit and 64 bit).

### Notes:

- For 64-bit SSO, only JRE is supported. For 32-bit SSO, either JRE or J# with .NET can be chosen.
- WebServices is required for Change Management with ENOVIA VPM V5 (LCA) Engineering Hub.
- For the Java Runtime Environment on Windows XP, the environment variable JAVA\_HOME has to be set on the Process Planning server to establish communication between it and Process Planning clients.
- To obtain the .NET Framework 3.0 redistributable, go to

<http://www.microsoft.com/downloads>

### Database-related Prerequisites

Oracle RDBMS Server Standard Edition or Enterprise Edition Version 10.2.0.2 or later is required to store data on the Manufacturing Hub server.

### Access to Product Information

Product information is delivered with the product CDs in HTML format. An HTML browser is required to access this documentation. Online

documentation may be installed and used only in the same supported operating environments as DELMIA Process Detailing and Validation.

- In a UNIX environment
- In a Microsoft Windows environment, one of the following browsers is required:

For AIX and HP-UX - Mozilla 1.7  
For Sun Solaris - Firefox 2.0

Microsoft Internet Explorer 7.0  
Firefox 2.0

In addition to a Java-enabled Web browser, the Java Plug-in at level 1.5 to search online documentation:

- For AIX, Java Runtime Environment version Java 1.5.0 SR6 can be downloaded from

<http://www.ibm.com/developerworks/java/jdk/aix/service.html>

- For HP-UX, Java Runtime Environment 5.0.10 can be downloaded from

<http://www.hp.com/go/java>

- For Sun Solaris, Java Runtime Environment Version 6, Update 4 can be downloaded from

<http://java.sun.com/products/archive/index.html>

- For Microsoft Windows, Java plug-in Version 6 Update 2 can be downloaded from

<http://java.sun.com/products/archive/index.html>

Although access to the online documentation might work on other HTML browsers, incidents specific to browsers other than those specified are not eligible for support.

## Prerequisites for the License Management Environment

### Process Detailing and Validation

Process Detailing and Validation applications must have an active LAN card (Ethernet or token ring) and TCP/IP installed and properly configured, even in the case of nodelock keys, though for nodelock there is no need to have the workstations connected to the network. No additional license management software is required when accessing nodelock license keys.

Dassault Systemes License Use Management (LUM) is required to serve concurrent license keys across a network. A LUM configuration file (i4ls.ini) is required on DELMIA Process Detailing and Validation clients to access concurrent license keys from these servers. Server and Nodelock license management mechanisms are available on all supported operating environments.

Dassault Systemes LUM level V4.6.8.3 is the minimum level.

The latest release of Dassault Systemes LUM V4, together with any applicable patches, can be downloaded at no charge from

<http://www.3ds.com/support/resource-library/>

## Process Planning

Process Planning applications require FlexLM 8.3b on the Manufacturing Hub server and Process Planning clients.

FlexLM technical information can be found at:

<http://www.3ds.com/support>

## Licensed Program Materials Availability

- Restricted materials - No. This licensed program is available without source licensed program materials. It is available in object code only.

## Supplemental Terms

### Type/Duration of Program Services (also referred to as "Support Services")

You will find all necessary information including processes, on Dassault Systemes web site :

<http://www.3ds.com/terms/support-policies>

### License Management for DELMIA Process Detailing and Validation

DELMIA Version 5 controls the number of concurrent users of a configuration or product, according to the number of license keys acquired for the configuration or product.

DELMIA Version 5 delivers identical license management mechanisms on UNIX and Windows environments, based on Dassault Systemes License Use Management (LUM). The following license management principles apply:

- A DELMIA Process Detailing and Validation configuration (standard or custom) will require a license key. License keys for configurations are acquired and released for the total configuration. The products within a configuration cannot be shared.
- Each shareable product will require a license key, in addition to one for the prerequisite configuration and any prerequisite product, if applicable.
- In all cases, configuration license keys are acquired at the beginning of the process and are released at its termination.
- Add-on (AOP) and shareable products may require license keys for prerequisite products that are not already included in a standard configuration. Prerequisites for shareable products can be satisfied by a standard configuration, by an AOP within a custom configuration, or by a shareable product. However, because all add-on products are defined within one custom license key, any AOP prerequisites must be satisfied by either a standard configuration or by other AOPs purchased and defined within the same custom configuration.
- LUM keys must be renewed, typically every two years. The actual duration will depend on the order details.

DELMIA Process Detailing and Validation can be used in three license management modes: nodelock, with concurrent usage of license keys on a network, or concurrent offline license management.

**Nodelock usage:** The use of a local display is mandatory for usage in nodelock mode. There is no limit to the number of processes launched for a given license key (configuration or product). For instance, a user can launch the following simultaneous processes:

- An interactive session
- A process executed through an OLE container application
- Replay of macros recorded from captured sequences of user interactions

In the nodelock mode of operation, only one license key per configuration and shareable product can be registered per machine, and only one user can run at a time on that machine. If multiple license keys per configuration or shareable product, or multiple users on a single machine, are required, refer to the **Concurrent usage** section.

**Concurrent usage:** A user on one machine on one display uses one license key per configuration or shareable product used, regardless of the number of processes. If the display changes, then an additional license key is taken for the corresponding process.

**Dynamic license management:** Shareable product license keys can be acquired and released during the session. (The ability to acquire and release licenses is not available for configurations.) Shareable license keys acquired at the beginning of the session cannot be released before the end of the session; only license keys dynamically granted upon user request during the session can be released during the session.

**Concurrent offline license management:** A concurrent license key control technique is available via the LUM server. It gives applications running on a Windows laptop the ability to disconnect from the license key server for a specific period of time.

During the checkout period, the server license key is unavailable for use by another concurrent user. This feature is designed to add additional flexibility to a user's work environment. It is offered to accommodate short-term travel needs and collaboration while away from a fixed office environment or server connection. All terms and conditions, including cross-border licensing terms, are unchanged, and users will check-out and check-in license keys at their home server, where rules and procedures are controlled by LUM.

### License Management for DELMIA Process Planning

Process Planning applications require FlexLM 8.3b on the Manufacturing Hub server and Process Planning clients for license management purposes. FlexLM supports three licensing methods:

- License file: A license file is supplied for each server and client based on the customer order.
- License server: The license server runs an NT-Service that manages a central license file for all servers and clients.
- Temporary license: The install process provides an option to create a temporary 30-day license. The license file is created after entering a license code.

### Educational Allowance Available

The standard educational allowance does not apply to DELMIA.

---

## Designated Machine Identification

No

---

## Test Period

No

---

## Use-Based Charges/Usage Restrictions

Charges for this program are based on the number of users logged on at any time. The total number of users logged on may not exceed the number for which you have been authorized. If the total number exceeds your authorization, you must notify Dassault Systemes and obtain additional authorizations.

---

## Softcopy Publications

The program that Dassault systemes licenses may include licensed publications in displayable or source form. Except as provided in this section, the terms and conditions of the license agreement with Dassault Systemes apply to these publications and to any copies that are made from them.

The licensed publications may be used in displayable or source form on all machines designated for this program. The licensed publications may also be copied and used on other machines in support of authorized use of this program.

To support authorized use of the Program, printed copies of the displayable or source material may be made if the copyright notice and any other legend of ownership is reproduced on each copy or partial copy.<sup>1</sup>

---

## Warranty

This program is warranted as specified in the Dassault Systemes license.

Licensed Program Specifications may be updated from time to time and such updates may constitute a change in specifications.

Following the discontinuance of all program services, this program will be provided "As Is" as specified in the Dassault Systemes license.

---

### Footnotes:

<sup>1</sup>

### Trademarks

Company, products and services names may be trademarks or services marks of related companies.



References in this publication to Dassault Systemes products, programs, or services do not imply that Dassault Systemes intends to make these available in all countries in which Dassault Systemes operates.

Any other documentation with respect to this licensed program, including any documentation referenced herein, is provided for reference purposes only and does not extend or modify these specifications.

March 2010